



LED  
INSIDE

INCASSI DA INTERNO  
INDOOR RECESSED LIGHT

## ALFA - MINIALFA

design Luce Lab

Corpo illuminanteda incasso a luce diretta, da soffitto o parete, con cornice a sezione tonda Ø100mm e Ø70mm. In metallo interamente verniciato bianco, nero, grigio e in cromo lucido o spazzolato con internogrigio. Disponibile, su richiesta, la versione con cornice in fogliaoro, argento o rame.




Utilizzabile su cartongesso o su laterizio con apposita cassaforma. L'apparecchio monta un modulo a tre LED CREE XT-E ed è disponibile in due temperature colore 3000K o 4000K. Disponibile in due versioni: con vetrino diffusore sabbiato o ottica ad apertura fascio 27°.

Recessed spotlight with direct light, both for ceiling and wall, with a round section frame Ø100mm and Ø70mm. Metal painted entirely white, black, grey and in polished or brushed chrome with grey inside. On request, available frame in gold, silver or copper leaf.

For plasterboard or brick wall with proper recessed box. The units equipped with three CREE XT-E LED module which is available in two colour temperatures: 3000K and 4000K. Available in two versions: with frosted glass or lens with optical beam angle 27°.

### ALFA

Ø 95





LED module 3 CREE XT-E 8W 700mA

IP40 IP43 F I A+ CE


Alimentatore non incluso / Power supply not included

CODE	FINISHINGS	LIGHT BEAM	COLOUR TEMPERATURE
T010 LA	01 02 03 04 05 DA *DO* RA *	A Frosted Glass	K3 3000K 580lm
T010 LA	01 02 03 04 05 DA *DO* RA *	A Frosted Glass	K4 4000K 700lm
T010 LA	01 02 03 04 05 DA *DO* RA *	M Lens 27°	K3 3000K 580lm
T010 LA	01 02 03 04 05 DA *DO* RA *	M Lens 27°	K4 4000K 700lm


#### PHOTOMETRICS



#### ACCESSORIES






TC008  
Cassaforma  
Recessed box



TE052 Driver 700mA 8W  
TE073 Driver 700mA 35W  
pag. 214

### MINIALFA

Ø 65





LED module 3 CREE XT-E 4W 350mA

IP40 IP43 F I A++ CE


Alimentatore non incluso / Power supply not included

CODE	FINISHINGS	LIGHT BEAM	COLOUR TEMPERATURE
T010 LB	01 02 03 04 05 DA *DO* RA *	A Frosted Glass	K3 3000K 330lm
T010 LB	01 02 03 04 05 DA *DO* RA *	A Frosted Glass	K4 4000K 400lm
T010 LB	01 02 03 04 05 DA *DO* RA *	M Lens 27°	K3 3000K 330lm
T010 LB	01 02 03 04 05 DA *DO* RA *	M Lens 27°	K4 4000K 400lm


#### PHOTOMETRICS



#### ACCESSORIES



TC007  
Cassaforma  
Recessed box



TE063 Driver 350mA 4W  
TE080 Driver 350mA 15W  
pag. 214

\* Finiture su richiesta / On request finishes