



ALIMENTATORI/DRIVER NON DIMMERABILI NOT DIMMABLE POWER SUPPLIES/DRIVERS




DRIVER INGRESSO 230V ca USCITA IN CORRENTE COSTANTE
DRIVER INPUT 230V ac OUTPUT COSTANT CURRENT

CODE	INPUT	OUTPUT	POWER	IP	DIM. (LxWxH)	N. MAX LAMP
TE063	90-264Vac	350mA	4W	IP20	68x35x21mm	1 (Minialfa, Minidelta)
TE080	100-250Vac	350mA	15W	IP20	138x40x29mm	1-4 (Minialfa, Minidelta)
TE052	220-240Vac	700mA	8W	IP20	58x35x21mm	1 (Alfa, Delta)
TE073	90-264Vac	700mA	35W	IP67	148x40x30mm	1-4 (Alfa, Delta)



DRIVER INGRESSO 230V ca USCITA 24V cc
DRIVER INPUT 230Vac OUTPUT 24V dc

CODE	INPUT	OUTPUT	POWER	IP	DIM. (LxWxH)
TE036	90-264Vac	24Vdc	20W	IP67	118x35x26mm
TE037	90-264Vac	24Vdc	35W	IP67	148x40x30mm
TE038	90-264Vac	24Vdc	60W	IP67	163x46x32mm
TE039	90-264Vac	24Vdc	100W	IP67	190x52x37mm
TE066	90-305Vac	24Vdc	150W	IP67	228x68x39mm
TE069	90-305Vac	24Vdc	240W	IP67	251x68x39mm
TE070	90-305Vac	24Vdc	320W	IP67	252x90x44mm




ALIMENTATORE INGRESSO 230V ca USCITA 12V PER ALOGENE
POWER SUPPLY INPUT 230Vac OUTPUT 12V FOR HALOGEN BULBS

CODE	INPUT	OUTPUT	POWER	IP	DIM. (LxWxH)
TE053	220-240Vac	12V	35-105W	IP20	128x38x31mm

Compatibile con lampada della gamma PARATHOM by Osram (GU4,GU5.3,G53)
Compatible with PARATHOM bulbs by Osram (GU4,GU5.3,G53 socket)

Dimmerabile a taglio di fase in discesa.
Dimmable by trailing-edge phase cut.



ALIMENTATORE INGRESSO 230V ca PER LAMPADE A SCARICA
POWER SUPPLY INPUT 230V ac FOR HID BULBS

CODE	INPUT	OUTPUT	POWER	IP	DIM. (LxWxH)
TE001	198-264Vac	250Vac	70W	IP20	155x83x32mm
TE002	198-254Vac	250Vac	150W	IP20	212x96x33mm