



ALIMENTATORI/DRIVER NON DIMMERABILI NOT DIMMABLE POWER SUPPLIES/DRIVERS



DRIVER INGRESSO 230Vca USCITA IN CORRENTE COSTANTE
DRIVER INPUT 230Vac OUTPUT CONSTANT CURRENT

CODE	INPUT	OUTPUT	POWER	IP	DIM. (LxWxH)	N. MAX LAMP
TE079	100-240Vac	500mA	12W	IP20	115x34x19mm	1 (Jisse, Tesco)
TE049	220-240Vac	500mA	25W	IP20	Ø72x24mm	1-2 (Jisse, Tesco)
TE052	220-240Vac	700mA	8W	IP20	58x35x21mm	1 (Jisse, Tesco)
TE072	90-264Vac	700mA	20W	IP67	118x35x36mm	1-2 (Jisse, Tesco)



ALIMENTATORE INGRESSO 230Vca USCITA 12V PER ALOGENE
POWER SUPPLY INPUT 230Vac OUTPUT 12V FOR HALOGEN BULBS

CODE	INPUT	OUTPUT	POWER	IP	DIM. (LxWxH)
TE053	220-240Vac	12V	35-105W	IP20	128x38x31mm

Compatibile con lampada della gamma PARATHOM by Osram (GU4, GU5.3, GU5.3)
Compatible with PARATHOM bulbs by Osram (GU4, GU5.3, GU5.3 socket)

Dimmerabile a taglio di fase in discesa.
Dimmable by trailing-edge phase cut.




ALIMENTATORE INGRESSO 230Vca PER LAMPAD E A SCARICA
POWER SUPPLY INPUT 230Vac FOR HID BULBS

CODE	INPUT	OUTPUT	POWER	IP	DIM. (LxWxH)
TE001	198-264Vac	250Vac	70W	IP20	155x83x32mm

DIMMER E ALIMENTATORI/DRIVER DIMMERABILI DIMMERS AND DIMMABLE POWER SUPPLIES/DRIVERS

**STRIPE
GO T5 E
T5 SEAMLESS**




ALIMENTATORE DIMMERABILE. Ingressi di controllo: DALI, TOUCH DIM
DIMMABLE POWER SUPPLY. Control inputs: DALI, TOUCH DIM

CODE	INPUT	ARTICLE	HOUSING	IP	TECHNICAL DATA	DIM. (LxWxH)
TE027	220-240Vac	Stripe	Inside product	IP20	1x14/24W T5	360x30x21mm
TE029	220-240Vac	Stripe	Inside product	IP40	1x21/39W T5	360x30x21mm
TE023	220-240Vac	Stripe	Inside product	IP20	1x28/54W T5	360x30x21mm
TE031	220-240Vac	Stripe	Inside product	IP20	1x35/49W T5	360x30x21mm
TE033	220-240Vac	Stripe	Inside product	IP20	1x80W T5	360x30x21mm


DIMMER E ALIMENTATORI/DRIVER DIMMERABILI DIMMERS AND DIMMABLE POWER SUPPLIES/DRIVERS

**COSTANT
CURRENT
LED
SUSPENSION**



DRIVER INGRESSO 230Vca USCITA IN CORRENTE COSTANTE. Ingressi di controllo: pulsante e IGBT-TRIAC
DRIVER INPUT 230Vac OUTPUT CONSTANT CURRENT. Control input: push button and IGBT-TRIAC


CODE	INPUT	OUTPUT	POWER	IP	DIM. (LxWxH)	N. MAX LAMP
TE088	198-264Vac	350mA	17W	IP20	166x46x34mm	
	198-264Vac	500mA	24W	IP20	166x46x34mm	1-2 (Jisse, Tesco)
	198-264Vac	700mA	32W	IP20	166x46x34mm	1-4 (Jisse, Tesco)



DRIVER INGRESSO 230Vca USCITA IN CORRENTE COSTANTE. Ingressi di controllo: pulsante, DALI e 1-10V
DRIVER INPUT 230Vac OUTPUT CONSTANT CURRENT. Control input: push button, DALI and 1-10V

CODE	INPUT	OUTPUT	POWER	IP	DIM. (LxWxH)	N. MAX LAMP
TE089	99-264Vac	350mA	40W	IP20	124x79x22mm	
	99-264Vac	500mA	50W	IP20	124x79x22mm	1-4 (Jisse, Tesco)
	99-264Vac	700mA	50W	IP20	124x79x22mm	1-6 (Jisse, Tesco)


**STRIPE
GO LED**



DRIVER INGRESSO 230Vca USCITA 24V PWM. Ingressi di controllo: DALI, TOUCH DIM
DRIVER INPUT 230Vac OUTPUT 24V PWM

CODE	INPUT	OUTPUT	HOUSING	POWER	IP	DIM. (LxWxH)
TE020	198-254Vac	24V PWM	Remote mounting	75W	IP20	220x47x44mm

**STRIPE
GO LED**




DIMMER MONOCANALE. Ingressi di controllo: PULSANTE 1+10 V
DIMMER ONE CHANNEL. Control inputs: PUSH BUTTON 1+10 V


CODE	INPUT	OUTPUT	HOUSING	POWER	IP	DIM. (LxWxH)
TE040	24Vdc	24V PWM	Remote mounting or DIN bar	192W	IP20	90x17x58mm

KIT DI EMERGENZA EMERGENCY KIT

**STRIPE
GO T5 E
T5 SEAMLESS**



KIT DI EMERGENZA PER LAMPAD E FLUORESCENTI
DIMMABLE POWER SUPPLY FOR FLUORESCENT LAMP



CODE	INPUT	ARTICLE	HOUSING	TECHNICAL DATA	SUPPLIED	DIM. (LxWxH)	BATTERY	DIM. (L2xW2xH2)	BFL (% LIGHTING FACTOR)
TE010	220-240Vac	Stripe go 120	Inside product	T5 28W	COMBO	425x30x21mm	NiMH 3h	336x26x26mm	12%
TE011	220-240Vac	Stripe go 120	Inside product	T5 54W	COMBO	425x30x21mm	NiMH 3h	396x26x26mm	6%
TE012	220-240Vac	Stripe go 150	Inside product	T5 36W	COMBO	425x30x21mm	NiMH 3h	396x26x26mm	13%
TE013	220-240Vac	Stripe go 150	Inside product	T5 49W	COMBO	425x30x21mm	NiMH 3h	336x26x26mm	6%
TE014	220-240Vac	Stripe go 150	Inside product	T5 80W	COMBO	425x30x21mm	NiMH 3h	396x26x26mm	4,8%