



INCASSI SENZA BORDI
RECESSED LIGHT FRAMELESS

STRIPE SYSTEM FRAMELESS LED

design Luce Lab


Sistema ad incasso frameless costituito da un profilo in alluminio al metro elettrificato con una o due strip led (19,2 W/m, 1520 lm/m), passo 2,5cm, e un diffusore in PMMA satinato. Lo starting kit, il diffusore, la lunghezza del profilo e il numero di moduli e/o accessori vanno specificati nell'ordine. Disponibile nella anodizzazione alluminio naturale spazzolato o verniciato bianco lucido. Disponibile in 3 temperature colore del bianco: K3, K4, K6 (caldo 3200K, neutro 4300K, freddo 6000K).

Recessed frameless system made up of an aluminium profile per meter electrified with one or two IP20 LED strips with high luminous flux 1520 lm/m (19,2 W/m), 2,5 cm pitch, and a satin PMMA diffuser. The starting kit, the diffuser, the length of the profile and the number of elements and/or accessories must be specified in the order. Available in the brushed natural anodized aluminium and shiny white finishings. Available in three white colour temperatures K3, K4, K6 (warm 3200K, neutral 4300K, cold 6000K).

LED
INSIDE


STRIPE FRAMELESS LED

MODULO AL METRO
ELEMENT PER METER



TS533 LZ

TS533 LA



TS534 LZ

TS534 LA



FORO / HOLE:
L_{tot} (mm) x 47
L_{tot} (mm) = $\sum L_1 + 9$ mm
MODULE L1=300÷3000

1 STRIP LED HI-POWER P.2,5 cm 19,2W/m 24Vdc

IP43 IP40 F

Alimentatore non incluso / Power supply not included

CODE	FINISHINGS	COLOUR TEMPERATURE	LUMINOUS FLUX
TS533 LZ	07 31	K3 3200K	1504lm/m
TS533 LZ	07 31	K4 4300K	1520lm/m
TS533 LZ	07 31	K6 6000K	1600lm/m
TS533 LA	07 31	STARTING KIT 1 STRIP HI POWER	

2 STRIP LED HI-POWER P.2,5 cm 19,2W/m 24Vdc

IP43 IP40 F

Alimentatore non incluso / Power supply not included


CODE	FINISHINGS	COLOUR TEMPERATURE	LUMINOUS FLUX
TS534 LZ	07 31	K3 3200K	3008lm/m
TS534 LZ	07 31	K4 4300K	3040lm/m
TS534 LZ	07 31	K6 6000K	3200lm/m
TS534 LA	07 31	STARTING KIT 2 STRIP HI POWER	



45




45




300 ÷ 3000


PHOTOMETRICS




COMPONENTS




Diffusore
Diffuser
TS506 XX
al metro / per meter



Staffa di giunzione
Metal junction bar
TS508



Alimentatore
Power Supply
pag. 108



Kit dimmerabile
Dimmable kit
pag. 108