


DIMMER E ALIMENTATORI/DRIVER DIMMERABILI DIMMERS AND DIMMABLE POWER SUPPLIES/DRIVERS


QUBA FLUO 50 QUBA FLUO 60



ALIMENTATORE DIMMERABILE. Ingressi controllo: DALI, TOUCH DIM
DIMMABLE POWER SUPPLY. Control inputs: DALI, TOUCH DIM

CODE	INPUT	ARTICLE	HOUSING	IP	TECHINAL DATA	DIM. (LxWxH)
TE026	220-240Vac	Quba fluo 50	Inside product	IP20	1x36W 2G11	360x30x21mm
TE023	220-240Vac	Quba fluo 60	Inside product	IP20	1x55W 2G11	360x30x21mm


STRIPE GO T5 E T5 SEAMLESS



ALIMENTATORE DIMMERABILE. Ingressi controllo: DALI, TOUCH DIM
DIMMABLE POWER SUPPLY. Control inputs: DALI, TOUCH DIM

CODE	INPUT	ARTICLE	HOUSING	IP	TECHINAL DATA	DIM. (LxWxH)
TE027	220-240Vac	Stripe	Inside product	IP20	1x14/24W T5	360x30x21mm
TE029	220-240Vac	Stripe	Inside product	IP40	1x21/39W T5	360x30x21mm
TE023	220-240Vac	Stripe	Inside product	IP20	1x28/54W T5	360x30x21mm
TE031	220-240Vac	Stripe	Inside product	IP20	1x35/49W T5	360x30x21mm
TE033	220-240Vac	Stripe	Inside product	IP20	1x80W T5	360x30x21mm


STRIPE GO LED



DRIVER INGRESSO 230Vca USCITA 24V PWM. Ingressi controllo: DALI, TOUCH DIM
DRIVER INPUT 230Vac OUTPUT 24V PWM. Control inputs: DALI, TOUCH DIM

CODE	INPUT	OUTPUT	HOUSING	POWER	IP	DIM. (LxWxH)
TE020	198-254Vac	24V PWM	Remote mounting	75W	IP20	220x47x44mm


STRIPE GO LED



DIMMER MONOCANALE. Ingressi controllo: pulsante, 1-10V
DIMMER ONE CHANNEL. Control inputs: push button, 1-10V


CODE	INPUT	OUTPUT	HOUSING	POWER	IP	DIM. (LxWxH)
TE040	24Vdc	24V PWM	Remote mounting or DIN bar	192W	IP20	90x17x58mm

COSTANT CURRENT LED WALL / CEILING



DRIVER INGRESSO 230Vca USCITA IN CORRENTE COSTANTE. Ingressi di controllo: pulsante e IGBT-TRIAC
DRIVER INPUT 230Vac OUTPUT COSTANT CURRENT. Control Input: push button and IGBT-TRIAC

CODE	INPUT	OUTPUT	POWER	IP	DIM. (LxWxH)	N. MAX LAMP
TE088	198-264Vac	350mA	17W	IP20	166x46x34mm	
	198-264Vac	500mA	24W	IP20	166x46x34mm	1-2 (Ulisse, Teseo)
	198-264Vac	700mA	32W	IP20	166x46x34mm	1-4 (Ulisse, Teseo, Glacier R1L), 1-2 (Glacier R2L)




DRIVER INGRESSO 230Vca USCITA IN CORRENTE COSTANTE. Ingressi di controllo: pulsante, DALI e 1-10V
DRIVER INPUT 230Vac OUTPUT COSTANT CURRENT. Control Input: push button, DALI and 1-10V


CODE	INPUT	OUTPUT	POWER	IP	DIM. (LxWxH)	N. MAX LAMP
TE089	99-264Vac	350mA	40W	IP20	124x79x22mm	
	99-264Vac	500mA	50W	IP20	124x79x22mm	1-4 (Ulisse, Teseo)
	99-264Vac	700mA	50W	IP20	124x79x22mm	1-6 (Ulisse, Teseo, Glacier R1L), 1-3 (Glacier R2L)

KIT DI EMERGENZA EMERGENCY KIT

QUBA FLUO



COMBO




BATTERY


KIT DI EMERGENZA PER LAMPADE FLUORESCENTI
DIMMABLE POWER SUPPLY FOR FLUORESCENT LAMP

CODE	INPUT	ARTICLE	HOUSING	TECHINAL DATA	SUPPLIED	DIM. (LxWxH)	BATTERY	DIM. (L2xW2xH2)	BFL (% LIGHTING FACTOR)
TE017	220-240Vac	Quba fluo 50 parete	Inside product	2G11 36W	COMBO	424x42x28mm	NIMh 3h	215x26x26mm	5,1%
TE075	220-240Vac	Quba fluo 60 parete	Inside product	2G11 55W	COMBO	424x42x28mm	NIMh 3h	336x26x26mm	8,5%

STRIPE GO T5 E T5 SEAMLESS



COMBO



BATTERY

KIT DI EMERGENZA PER LAMPADE FLUORESCENTI
DIMMABLE POWER SUPPLY FOR FLUORESCENT LAMP

CODE	INPUT	ARTICLE	HOUSING	TECHINAL DATA	SUPPLIED	DIM. (LxWxH)	BATTERY	DIM. (L2xW2xH2)	BFL (% LIGHTING FACTOR)
TE010	220-240Vac	Stripe go 120	Inside product	T5 28W	COMBO	425x30x21mm	NIMh 3h	336x26x26mm	12%
TE011	220-240Vac	Stripe go 120	Inside product	T5 54W	COMBO	425x30x21mm	NIMh 3h	396x26x26mm	6%
TE012	220-240Vac	Stripe go 150	Inside product	T5 35W	COMBO	425x30x21mm	NIMh 3h	396x26x26mm	13%
TE013	220-240Vac	Stripe go 150	Inside product	T5 49W	COMBO	425x30x21mm	NIMh 3h	336x26x26mm	6%
TE014	220-240Vac	Stripe go 150	Inside product	T5 80W	COMBO	425x30x21mm	NIMh 3h	396x26x26mm	4,8%