





INCASSO A SCOMPARSA TOTALE A LED RECESSED LED LIGHT FRAMELESS

Max 1560 lm/m - 19,2 W/m - Passo 2,5 cm - 240 led/m


		CODICE CODE	L1 (mm)	DATI TECNICI TECHNICAL DATA	KELVIN KELVIN	COLORI COLOURS	FORO/HOLE Ltot (mm) x 47mm
	Modulo incasso a scomparsa con supporto per applicazione strip led <i>Frameless recessed element with support for strip led application</i>	TS 535LA	585			07 - 31	 $L_{tot} (mm) = \sum L1 \text{ dei moduli/ of elements } + 9 \text{ mm}$
		TS 535LB	885			07 - 31	
		TS 535LC	1185			07 - 31	
		TS 535LD	1485			07 - 31	
		TS 535LE	2370			07 - 31	
		TS 535LF	2970			07 - 31	
	Modulo strip led singola IP20 con sistema brevettato magnetico <i>Single led module strips IP20 with patented magnetic system</i>	TS 537LA	575	1xStrip LED	K3-K4-K5		
		TS 537LB	875	1xStrip LED	K3-K4-K5		
		TS 537LC	1175	1xStrip LED	K3-K4-K5		
		TS 537LD	1475	1xStrip LED	K3-K4-K5		
		TS 537LE	2350	1xStrip LED	K3-K4-K5		
		TS 537LF	2950	1xStrip LED	K3-K4-K5		
	Modulo strip led doppia IP20 con sistema brevettato magnetico <i>Double led module strips IP20 with patented magnetic system</i>	TS 538LA	575	2xStrip LED	K3-K4-K5		
		TS 538LB	875	2xStrip LED	K3-K4-K5		
		TS 538LC	1175	2xStrip LED	K3-K4-K5		
		TS 538LD	1475	2xStrip LED	K3-K4-K5		
		TS 538LE	2350	2xStrip LED	K3-K4-K5		
		TS 538LF	2950	2xStrip LED	K3-K4-K5		
	Driver	TE037		Driver 24V - 35W			
		TE038		Driver 24V - 60W			
	Driver	TE039		Driver 24V - 100W			
	Dimmer	TE040		Dimmer 24V - 6A (144W)			
		TE041		Dimmer "3 Zone" 240W			
	Dimmer	TE043		Telecomando radiofrequenza per T041 RF remote control for TE041			



Profilo stretto
Narrow profile



IP40



Facilità di manutenzione
Easy maintenance